

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	239159	(ccd or sensor or detector) and (lens or lenses)	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TD B
2	BRS	L2	70642	(spring or flex\$5 or bias\$3) and 1	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TD B
3	BRS	L3	44013	circuit and 2	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TD B

	Type	L #	Hits	Search Text	DBs
4	BRS	L4	5447	circuit same opening and 3	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TD B
5	BRS	L6	1401	(ccd) and (lens or lenses) and 4	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TD B
6	BRS	L5	1045	circuit near4 opening and 3	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TD B

	Type	L #	Hits	Search Text	DBs
7	BRS	L7	272	(ccd) and (lens or lenses) and 5	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TD B